KISCLEANER ULTRA

Cleaners for Remedial Waterproofing Products

DESCRIPTION

Kiscleaner Ultra is a mixture of solvent and lubricant for use of cleaning of equipment using Kensetsu remedial waterproofing range of products – such as KisEpo 20, KisGel P1 etc. This is universally effective for most polyurethane and epoxies systems.

RECOMMENDED USE

- To clean substrates from overflow or spills
- To flush and prepare injection pumps
- To clean equipment used with Kensetsu polyurethane remedial waterproofing products.

ADVANTAGES

- Highly efficient
- Lubricating

PACKAGING

Kiscleaner Ultra is supplied in 10 kg per pail

APPLICATION GUIDELINES

a) Application

- The pumps should be flushed with Kiscleaner Ultra and then dry before injection.
- The cleaner must be discharged before injection with resin.

b) Cleaning

- All tools and equipment should be cleaned with KISCLEANER ULTRA immediately after use.
- KISCLEANER ULTRA should be used before the resin has hardened. The pumps should be cleaned by recirculation for at least 1 minutes and the then another round of flushing should be carried out with fresh cleaner.

STORAGE

Kiscleaner Ultra should be stored at room temperature, min 10°C and max 38°C, kept dry and out of direct sunlight. 12-month shelf life can be expected from date of manufacturing if recommended storage condition is respected.

HEALTH & SAFETY

Refer to SDS for further information.

DATA SPECIFICATION SHEET

TECHNICAL PROPERTIES

KISCLEANER ULTRA	
Appearance	Transparent
Viscosity at 25°C Brookfield dv sp.2 60rpm	20-50 cps
Density (Unreacted)	1.25 g/mL
Freezing Point	-50°C
Flash Point	>120 °C