



KisTop PT

DESCRIPTION

KISTOP PT is a quick curing solvent based protective coat for all prepared surface.

RECOMMENDED USE

- Exposed Carpark decks, loading bay

ADVANTAGES

- Fast drying
- Excellent adhesion
- Excellent chemical and solvent resistance
- Excellent weather resistance

Coverage

1 set of 5 kg will cover estimated 6m² (1 coat), We recommend to apply 2 coats

TECHNICAL PROPERTIES

KisTop PT	
Appearance / Colour – on request	Base – Part A
	Hardener - Part B
Mixing Ratio	Part A: Part B = 4:1 by weight
Flashpoint	23 °C
Induction period	15 minutes with intermittent stirring at 30 °C
Pot Life	4 hours at 30 °C

PACKAGING

Part A – 4 kg

Part B – 1 kg

STORAGE

KisTop PT should be stored in tightly sealed original packing and a 12-month shelf life can be expected from date of manufacturing.

HEALTH & SAFETY

Refer to SDS for further information.

IMPORTANT NOTES

Any information and/ or specification contained herein is to the best of the company knowledge, true and accurate, it is always recommended that trial to be carried out to confirm suitability of use for all products, as no warranty is given or implied in connection with any recommendations and/or suggestions made by the company representatives, agents and/or distributors.

All information contained in this document is effective from date shown and supersedes all previous version. Please check with your local KENSETSU office to confirm that this is up to date version.