

KisCote FE (Part A)

1 IDENTIFICATION OF THE SUBSTANCE/PREPERATION AND OF THE COMPANY UNDERTAKING

PRODUCT NAME KisCote FE (Part A)

APPLICATION 2 Part Water Based Epoxy Coating SUPPLIER Kensetsu International (S) Pte Ltd

No.7 Mandai Link #09-24 Mandai Connection Singapore 728653 sales@kst-grp.com

CONTACT TELEPHONE Phone: (65) 6255 6855 (not in use for 24hours)

Fax: (65) 6255 5755

2 HAZARDS IDENTIFICACTION

GHS CLASSIFICATION

Physical and Chemical Hazards Not classified.

Human health Acute toxicity (oral) 4 - H302; Skin Corrosion/Irrit. 2 - H315; Skin Sens. 1 - H317;

Environment Aquatic Chronic 2 - H411

LABEL IN ACCORDANCE with GHS



SIGNAL WORD	Warning	
HAZARD STATEMENTS:	H302	Harmful if swallowed.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H411	Toxic to aquatic life with long lasting effects.
PRECAUTIONARY STATEMENTS	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P270	Do not eat, drink or smoke when using this product.
	P272	Contaminated work clothing should not be allowed out of
	0070	workplace.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/
		face protection.
	P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
	P302+P352	IF ON SKIN: Wash with plenty of soap and water.
	P312	Specific treatment.

Rinse mouth.

P330



SAFETY DATA SHEET KisCote FE (Part A)

P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before use

Wash contaminated clothing before use.

P391 Collect spillage.

P501 Dispose of content/container in accordance with

local/national/international regulation. Other hazards which

do not result in classification: (NFPA Classification)

3 COMPOSITION/INFORMATION ON INGREDIENS

REACTIVE DILUENTS	20 – 40%
CAS-No: 68609-97-2	
BISPHENOL-A TYPE EXPOXY RESIN	60 - 80%
CAS-No: 25068-38-6	

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

Do not induce vomiting. Get medical attention immediately.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Seek medical advice immediately if develop skin inflammation.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: seek medical attention and bring along these instructions.

5 FIRE-FIGHTING MEASURES

EXTINGUSHING MEDIA

Carbon dioxide, powder, foam or water fog. Do not use water jets.

SPECIFIC EXPOSURE HAZARDS

Toxic fumes.

PROTECTIVE MEASURES IN FIRE

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.



KisCote FE (Part A)

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. Do not smoke, use open fire or other sources of ignition.

ENVIRONMENT PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environment Agency or other appropriate regulatory body. Avoid discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Clear with liquid absorbent or contain and remove by best available means. Contact local industrial waste disposal company for disposal.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feeding stuffs.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROCTECTIVE EQUIPMENT





OCCUPATIONAL EXPOSURE LIMIT

None assigned.

ENGINEERING CONTROL MEASURES

Provide adequate ventilation, including appropriate local extraction.

HANDS PROTECTION

Use chemical resistant gloves classified under Standard EN374.

EYE PROTECTION

Use EN166 or equivalent safety goggles (with side shield).

HYGIENE MEASURES

Wash hands at the end of each work shift and before eating, smoking and using the toilet.

SKIN PROTECTOR

Wear apron or protective clothing in case of contact.



KisCote FE (Part A)

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Vicious Liquid
COLOUR Clear to pale yellow

RELETIVE DENSITY @ 20°C 1.17

WATER SOLUBILITY Not miscible

FLASH POINT (CLOSED,°C) >200

AUTO FLAMMABILITY (°C) Auto ignition temperature: >200

VAPOUR PRESSURE (kPa @ 20°C) < 0.01

10 STABILITY AND REACTIVITY

STABILITY

Stable when react with compound containing amino, hydroxyl or carbon groups to give stale, cross linked materials.

CONDITIONS TO AVOID

Not known

MATERIALS TO AVOID

Strong acids, strong alkalis, strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition. Oxides of carbon. Irritant fumes.

11 TOXICOLOGICAL INFORMATION

Information on the likely routes of exposure:

(Respiratory) - Not available

(Oral) - Harmful if swallowed (Eye Skin) - Causes skin irritation

May cause an allergic skin reaction

Delayed and immediate effects and also chronic effects from shorts and long term exposure:

Acute toxicity

*Oral - [4,4'-(1-methylethylidene)bisphenol polymer with (Chloromethyl)oxirane]:

LD50 > 1000 mg/kg Rat

*Dermal - [4,4'-(1-methylethylidene)bisphenol polymer with (Chloromethyl)oxirane]:

LD50 > 20000 mg/kg Rabbit

*Inhalation - Not available

Skin corrosion/irritation - Causes skin irritation
Serious eye damage/irritation - Not available
Respiratory sensitization - Not available

Skin sensitization - May cause an allergic skin reaction
Carcinogenicity *IARC - Not available

*OSHA - Not available
*ACGIH - Not available
*NTP - Not available
*EU CLP - Not available



KisCote FE (Part A)

12 ECOLOGICAL INFORMATION

ECO-TOXICITY

Fish - [4,4'-(1-methylethylidene)bisphenol polymer with (Chloromethyl)oxirane]:

LC50 = 1.41 mg/l 96 hr Oryzias latipes

Crustaceans - [4,4'-(1-methylethylidene)bisphenol polymer with (Chloromethyl)oxirane]:

LC50 = 1.7 mg/l 48 hr

Algae - Not available

PERSISTENCE AND DEGRADABILITY

Persistence - [4,4'-(1-methylethylidene)bisphenol polymer with (Chloromethyl)oxirane]:

log Kow = 2.821 (Estimates)

Degradability - Not available

BIOACCUMULATIVE POTENTIAL

Bioaccumulative potential

[4,4'-(1-methylethylidene)bisphenol polymer with (Chloromethyl)oxirane]:

BCF = $0.56 \sim 0.67$ (Exposure concentrates: 10 ug/1, 5.6 < =

BCF = <6.8 (Exposure concentrations: 1ug/1)

BIODEGRADATION

[4,4'-(1-methylethylidene)bisphenol polymer with (Chloromethyl)oxirane]:

Biodegradability = 0 (%) 28 days

Mobility in soil - Not available

Other adverse effects - Not available

13 DISPOSAL CONSIDERATION

GENERAL INFORMATION

Dispose of through an authorized waste contractor to a licensed site, be react with resin component to give an inert polymeric material.

DISPOSAL METHODS

Disposal of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFOMATION

Classification for ROAD and RAIL Transport (ADR/RID):

UN Number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Epoxy Resin)

Class : 9
Packing group : III
Label(s) : 9
Marine Pollutant : Yes

Classification for SEA Transport (IMO/IMDG):

UN Number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Epoxy Resin)



SAFETY DATA SHEET KisCote FE (Part A)

Class : 9
Packing group : III
Label(s) : 9
Marine Pollutant : Yes

Classification for AIR Transport (IATA/ICAO):

UN Number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Epoxy Resin)

Class : 9
Packing group : III
Label(s) : 9
Marine Pollutant : Yes

15 REGULATORY INFOMATION

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations:

This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Workplace Classification:

This product is classified as hazardous according to Singapore Standards, Act and Regulations.

The following statues, regulations and standards have the related prescribes on chemicals in terms of safe use, storage, transportation, loading and unloading, classification and symbol etc.:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations Environmental Protection and Management Act and Environmental Protection and Management (Hazardous Substance) Regulations.

Chemicals Weapon Prohibition Act

Fire Safety Act and Fire Safety (Petroleum and Flammable Materials) Regulations.

16 OTHER INFOMATION

REVISION DATE REV. NO. SDS-FE-a V2 DATE 15/02/2022

DISCLAIMER

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. KENSETSU INTERNATIONAL (S) PTE LTD shall not be held liable for any damage resulting from contact with or handling of the above products.